



CONSTRUCTION :

- Die-cast aluminum housing
- Metal impeller or Glass fiber reinforced plastic: Impeller are UL 94V-0 rating
- Shaded pole motor
- Impedance protected
- Leader wire or Terminal is available

OPERATING TEMPERATURE :

Ball bearing - 30°C to +75°C
 Sleeve bearing - 10°C to +70°C


WEIGHT :

600 grams Specifications are subject to change without notice

Specifications

MODEL NO.	BEARING	RATED VOLTAGE	FREQUENCY	MAX. RATED CURRENT	MAX. INPUT POWER	SPEED	MAX. AIR FLOW		MAX. AIR PRESSURE		NOISE
		VAC	Hz	mA	W	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	
4E-115B-17	Ball	115	50/60	210/200	21/19	1600/1700	1.5/1.7	52.3/58.4	2.4/2.7	0.1/0.1	25/30
4E-115S-17	Sleeve										
4E-230B-17	Ball	230	50/60	120/110	19/18	1600/1700	1.5/1.7	52.3/58.4	2.4/2.7	0.1/0.1	27/32
4E-230S-17	Sleeve										
4E-115B-21	Ball	115	50/60	230/220	22/20	1800/2100	1.7/1.8	60/65	5.2/6.1	0.2/0.2	36/38
4E-115S-21	Sleeve										
4E-230B-21	Ball	230	50/60	130/120	20/19	1800/2100	1.7/1.8	60/65	5.2/6.1	0.2/0.2	36/38
4E-230S-21	Sleeve										
4E-115B-25	Ball	115	50/60	240/230	23/21	2250/2500	2.0/2.2	70/78	6.5/7.3	0.3/0.3	38/42
4E-230B-25	Ball										
4E-230S-25	Sleeve	230	50/60	130/120	21/20	2250/2500	2.0/2.2	70/78	6.5/7.3	0.3/0.3	38/42
4E-240B-25	Ball	240	50/60	130/120	21/20	2250/2500	2.0/2.2	70/78	6.5/7.3	0.3/0.3	38/42
4E-115HB	Ball	115	50/60	250/240	24/22	2650/3000	2.2/2.3	77.5/89	6.0/6.0	0.3/0.3	42/46
4E-115HS	Sleeve										
4E-230HB	Ball	230	50/60	140/130	22/21	2650/3000	2.2/2.5	77.5/89	6.0/6.0	0.2/0.2	42/46
4E-230HS	Sleeve										
4E-DVB	Ball	115/230	50/60	200/120	22.2/21.2	2650/3000	2.2/2.5	77.5/89	6.0/6.0	0.2/0.2	42/46
4E-DVS	Sleeve										

Dimensions (mm)



Performance Curve

